

## **RELIC SPECIFICATION SHEET**

PHYSICAL PROPERTIES

U.S. Units

Metric Units

Total Weight: Fabric Weight: Vinyl Weight: Thickness: Adhesive: Fabric: 20 oz per linear yd 2.7 oz per linear yd 17.0 oz per linear yd 0.015 to 0.030 in 0.3 oz per linear yd

620.06g per linear meter 83.71g per linear meter 527.06g per linear meter 0.38 to 0.76mm

9.03g per linear meter

Highly reflective surface in silver

Polyester / vinyl face with non-woven backing

PRODUCT PACKAGING

Material Width: Core Diameter: 54 inches (+/- 1/8 inches) 3 inch ID Heavy Duty

SPECIFICATIONS TESTING CERTIFICATION Federal Specification: WA Specification:

CCC-408-D Type II Class A W-101 Type II Class A

FIRE TESTING

NFPA Life Safety Code 101: Class A ASTM-E84 Tunnel Test: Class A

CAN/ULC-S102.2: Passed all requirements

NFPA 286 Corner Burn Test: Class A

BS476 Parts 6 & 7: Passed all requirements
EU Class Flame (EN 15102): Passed Class B, s2
ASTM-G21 Specification: Passed all requirements

Made with Low VOC vinyl

Tested per CA-1350 Air Quality Standards Cadmium & Lead Free Formulation Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover



28 rue Jacob 75006 Paris +33 (0)1 43 29 40 05 contact@triodedesign.com www.triodedesign.com